




(303) 466-4206
Fax – (303) 466-1810

The Gas Connection, Inc.

THE GAS CONNECTION, INC.
GENERAL FIREPIT SPECIFICATIONS & PRICING



Note: For proper operation & dependability, please consider these specifications.

WT	= Wall Thickness (8" to 12") Average
ID	= Inside Diameter (36") Average
WH	= Wall Height Average (20" to 24")
Air Intake/Drain Holes	= Need min. 32 square inches for air intake & drainage. Total square inches can be in 2 to 4 equal areas located at the base of the firepit.

(A variety of shapes and sizes are possible)

Important: For "built in" firepits to have adequate flame height, the gas line must originate from the gas meter. It is recommended to leave 2 to 4 drain/air holes evenly spaced around the bottom of the firepit equaling 32 sq. inches total. It is also recommended to leave a **1 1/4 I.D. sleeve** for the key valve above the drain/air holes, but 6" or less from grade.

FIREPIT INSTALLATION PROCEDURES

Steps:

- Step 1:** Contractor / Owner digs a 24" deep trench from meter to firepit location. Note: Trenching is available.
Step 2: The Gas Connection, Inc. installs the gas line from the gas meter to the firepit location.
Step 3: (After inspection) Contractor / Owner to finish building patio and firepit wall.
Step 4: The Gas Connection, Inc. returns to do final piping, key valve, burner, grate, rock and set-up (key valve, grate, burner and rock to be supplied by The Gas Connection, Inc.)

NOTE: It is important to install the gas line before the patio is built!