

Thank You For Choosing The Gas Connection, Inc.

We appreciate your business and want you to be happy with your purchase. Here are some tips to help you feel comfortable with the operation of your gas log unit.

LIGHTING THE PILOT LIGHT




Gas Logs Only

- Always follow the safety instructions on or with your unit. These safety advisement's and lighting instructions supersede any verbal or written information provided by The Gas Connection, Inc. **CALL THE GAS CONNECTION IF YOU SMELL GAS.**
- Make sure all safety valves are turned fully on.
- Push in gas knob slightly and turn clockwise to the "off" position.
- Wait 5 minutes to clear out any gas. If you then smell gas (including near the floor) call The Gas Connection and close the emergency shut off valve. If you don't smell gas move on to the next step.
- Turn the control knob counter clockwise to the "pilot" position. (Probably ¼ turn.)
- Hold a match or a lighter right at the pilot light and push the control knob in fully and hold. If the pilot does not light in 3 minutes, call The Gas Connection, Inc. If the pilot does light, continue holding the knob for 1 minute after the pilot lights.
- Release the control knob. The pilot should remain lit. If not, repeat steps 3 – 5. If after several tries, the pilot won't stay lit, call The Gas Connection.
- To turn you gas log set on; turn the control knob counter clockwise to the "on" position (Probably ¼ turn.)
- To turn your gas set off; turn the control knob clockwise to the "pilot" position. This will leave the pilot lit, if you turn the control knob all the way to the "off" position, the pilot will go out.

****Important** Gas logs must be operated with the glass doors fully open and for 30 minutes after burning.****

SHUTTING OF THE GAS TO YOUR UNIT

In the event you smell gas, we have install an emergency manual shut off valve by which you turn off the gas to your unit.

Diagram of your control knob positions	
	Pilot Position Pilot is on. The Flames are off.
On Position Pilot and the flames are on. 90° counter clockwise from Pilot position.	
	Off Position Flames and the pilot are off. Push in and turn 90° from pilot position.
We recommend that you leave your pilot burning at all times.	

Your emergency valve is a:

Floor Valve Wall Valve Inline

Floor/Wall Valve

1. To turn the shut off valve off, insert the key into the valve opening and turn to the right (clockwise) until it stops.
2. To turn the shut off valve on, simply turn the key to the left (counter clockwise) until it stops.

Note: To prevent damage to the shut off valve, do not over tighten in either direction, also keep the key in a safe place near you fireplace. Do not leave the key in the wall or floor valve.

Inline Shut off Valve

1. To turn the gas off, turn the handle 90° clockwise (perpendicular to the gas pipe).
2. To turn the gas on, simply turn the handle 90° counter clockwise so it is parallel with the gas pipe.

The Gas Connection, Inc. offers a three month warranty on installation and a one month warranty on service, valid from the date of installation. The warranty will cover any problems which occur with the unit. It does not cover the relighting of the pilot light, which is provided at our regular service charge. Payment must be received at the time of the final hook-up to validate the warranty.

If you have further questions, or require further assistance, please call or office at (303) 466-4206